

SPECIFICATION

Electronic Version 1.2.8

Stylesheet Version 1.0

System for High Density Linear Serpentine Data Recording

Background of Invention

- [0001] Several methods to record data on magnetic tape are known. Among those are helical scan, arcuate scan, and linear recording. The present invention relates to linear recording.
- [0002] A typical tape drive for linear recording is shown in *Fig 1*. It comprises of a supply reel 2 and a take up reel 3. One or both reels may be enclosed in a cartridge. The tape 6 is moved under the control of a servo system (not shown) between the supply reel and the take up reel past a read-write head 10. A plurality of bearings 4 may be used to guide the tape.
- [0003] Linear recording devices write the data in individual data tracks parallel to the edge of the recording media. *Fig 2* depicts a typical configuration. Recording media 6 is moved in direction of arrow D1 across the surface of a read/write head 10. The head contains several write elements 11, each of which writes one data track 12 on magnetic tape 6. The head also contains a number of read elements 13. Typically, there are one or two read elements for each write element.
- [0004] When retrieval of previously recorded data from tape is desired, the media is moved again across the head and the read elements 13 receive the magnetic signal from the media and generate electrical signals that can be decoded by appropriate circuitry. The read elements are also used during a recording operation to ensure that data has been recorded correctly. After the media has moved past the write elements 11 and data has been recorded, the media moves past the read elements 13. The data of each track is read and compared to the data that was written onto that track. Any recording error is detected and an appropriate error correction procedure can be

be located adjacent to the second group, and so on. The tape will be recorded in this manner from the middle of the tape, in an alternating fashion, towards both edges.

[0009] *Fig 3b* shows another variation. The elements of the head are spaced further apart so that a row of elements may span, for example, $\frac{1}{4}$ of the width of the tape. The data are written in four track groups 20, 30, 40, and 50. In the example in *Fig 3b* the recording of track group 20 has been completed. Track group 30 is in the process of being recorded, while track groups 40 and 50 have not been recorded yet. In this example four tracks are written simultaneously. In a different embodiment the number of tracks written simultaneously may differ and the distance between the tracks may also differ.

[0010] The process of recording track group 30 will now be described. The recording of the other 3 groups follows the same method as the recording of track group 30.

[0011] After writing the first set of tracks 31, 32, 33, and 34, while the tape is moved in direction of *D1*, the head (not shown) is moved by a small increment and tracks 35, 36, 37, and 38 are written while the tape is moved in direction *D2*. Thereafter the head is moved again and the next set of tracks (not shown) is written in direction *D1*. This process is repeated until the area between the original tracks is recorded. After this section of the tape has been recorded, the head is moved by a large distance and track group 40 is recorded. Thereafter the head is moved again by a large distance and of track group 50 is recorded.

[0012] Independent of the particularity of the implementation of the serpentine recording, there are several disadvantages that are common to all implementations. *Fig 4* shows two positions of the read/write head 10. At position *P1* the track group nearest to the upper edge of the tape is recorded or read. The location of the read and write elements is shown by outline 14. At position *P2* the track nearest to the lower edge of the tape is recorded or read. The surface of the head must support the tape 6 in either position. The length *L* of the head must be substantially twice the width *w* of the tape 6.

[0013] *Fig 5* shows a head 60 that has a surface 61 over which the tape (not shown) is moved. A plurality of write elements 62 are grouped closely together. The spacing of

head before the entire tape is recorded. The high number of passes, combined with the lack of verification, poses a serious risk to the reliability of the data.

[0021] It is now clear that an improved read/write head is desired.

[0022] It is an object of the present invention to reduce the size of the read/write head to allow miniaturization of the tape drive.

[0023] It is another object of the present invention to reduce the mass of the head to improve the frequency response of the track-following system.

[0024] It is another object of the invention to control the separation between the head and the tape.

[0025] It is another object of the invention to reduce the tape and the head wear.

[0026] It is another object of the invention to reduce the tape and the head contamination.

Summary of Invention

[0027] The read and write elements of the inventive head are contained in a housing that is only slightly larger than the row of recording elements. The size of the head substantially matches the width of one recording group and is significantly smaller than the width of the tape.

[0028] The head and the actuator are designed so that the head will fly over the moving tape. The head is pushed against the tape by a force to minimize and to control the flying height of the head over the tape. The tape is stabilized to provide a uniform surface for the head. The device used to stabilize the tape may be a hydrostatic bearing, a hydrodynamic bearing, a second read-write head, a roller bearing, or another suitable device.

Brief Description of Drawings

[0029] Fig 1 is an illustration of prior art showing a typical tape drive. (previously described)

[0030] Fig 2 depicts a prior art example of linear recording. (previously described)

- [0048] Fig 13 a shows the side view before the head is moved.
- [0049] Fig 13b shows a new position of the head when rods enter sloped guides.
- [0050] Fig 13c shows the head position after the rods further entered the sloped guides.
- [0051] Fig 13c shows the head position after the head has been moved from the tape path.

Detailed Description

- [0052] *Fig 6* shows an exemplary tape drive with the inventive head assembly 70 . A take-up reel 3 , two tape guides 4 , and a tape cartridge 5 with an enclosed supply reel (not shown) are mounted on a base 7 . The tape (not shown) is wound from the supply reel in cartridge 5 over two tape guides 4 to the take-up reel 3 past the read-write head assembly 70 . The head assembly 70 is shown in greater detail in *Fig 7a* .
- [0053] A base 71 contains an actuator that is capable of moving the read-write head in the directions of arrow A . Actuators of many different designs are known. Voice coil driven actuators are used in high performance tape drives because of their ability to move the head at a high speed and with a fast acceleration. They can be designed to move the head over the required length so that the head elements can access all recorded areas of the tape. Actuators using piezo elements are also very fast but have a limited operating range. Actuators using motor driven lead screws are able to move the head over the required range but they are very slow. They are therefore generally used in low performance, low-density, tape drives. They are also used in high performance tape drives in combination with voice coil actuators and piezo actuators. The lead screw is used to move the head to the desired track group. Typically this is done only at the beginning of tape and at the end of tape. While tape is moving, the piezo actuator or the voice coil actuator is used to for closed loop track following. Other designs in addition to the above-described actuators are used and may be used in the future. The present invention is independent from the type of actuator used.
- [0054] Referring now to *Figs 7a* and *7b* , the housing 71 containing the actuator has two openings 77 . Flexures 72 and 76 are movably attached to the actuator through the openings 77 . Flexure 72 has read-write head 74 attached, and flexure 76 has tape-

guiding block 75 attached. The actuator moves the flexures with the attached head and guide block laterally to the tape as indicated by arrow A. The tape 6 is positioned between the head 74 and the tape-guiding block 75 as shown in *Fig 7b*. Load springs 73 and 78 push head and the tape-guiding block towards each other. In the preferred embodiment the surface of the head block matches the surface of the tape-guiding block. It is important that the head remains in close contact with the tape. This requires that the head and the tape-guiding block are substantially parallel to each other. The flexures allow movement of the head block and the tape-guiding block. Under the pressure of the springs, the surfaces of both blocks will be substantially parallel. Use of flexures combined with the springs is very advantageous, because manufacturing tolerances, wear of components after prolonged use, and other factors do not disturb the alignment of the read-write head to the tape-guiding block.

[0055] The tape generates air currents around it as it moves. As tape speed increases the air currents moving with the tape cause an air film to develop between the head surface and the tape, lifting the head off the tape surface. This separation between the tape and the recording head must be very accurately controlled. A very small separation can be tolerated and may even be desirable to reduce the friction between the tape and the head and to thereby reduce the tape and the head wear. With increased recording density, the distance of the separation between the tape and the recording head must be kept within tight parameters. In order to decrease recording time the speed of the tape has been increased in newer tape drives. The increased tape speed may cause an increase of the thickness of the air cushion between the head and the tape and therewith creates an even wider separation of the head and the tape. By selecting springs 73 and 78 with sufficient force to counteract the separating force of the air cushion, the separation of the head and the tape can be kept to a desired minimum for any tape speed and for any tape tension.

[0056] It is an additional advantage of the invention that a second read-write head can replace tape-guiding block 75 if dual-sided recording is desired.

[0057] *Fig 8* illustrates the size of the read-write head. While the tape is moving in direction of arrow D1, track group 79 is accessed. Track group 79 consists of a plurality of data tracks. The data tracks may be recorded or read simultaneously, or

moving tape generates an air film 91 that separates the tape 6 from the surface 90 of the hydrodynamic bearing and tape "flies" over the stabilizer. For added stability and column strength of the tape, the tape is preferably moved over the stabilizer at an angle α . The desired wrapping angle depends on many parameters.

- [0061] The surface 90 is preferably made of a material that limits the wear of the tape during the start and stop operation. Tape tends to stick to surfaces, especially in humid and hot environments. The surface should therefore be such that it prevents such sticking.
- [0062] *Fig 10b* shows a dual bump hydrodynamic bearing. Each bump 92 acts as a hydrodynamic bearing. Tape is stabilized in area 93 between the bumps.
- [0063] *Fig 10c* shows a hydrostatic bearing. Pump 94 compresses air that is cleaned by filter 95. The pressurized air escapes through small openings in the bearing surface 96 and generates an air film that separates the tape from the bearing surface 96.
- [0064] In *Fig 10d* a roller 97 is used to stabilize the tape 6. In the preferred embodiment the roller surface 98 is made of porous material. The porous material prevents the development of an air film between the roller and the tape.
- [0065] A variation of the above method is shown in *Figures 11a* and *11b*. Instead of a stabilizer a second flexure 88 is added. Flexure 88 is biased against flexure 87. Flexure 88 holds tape-guide block 87. As described above, a second read-write head may replace the tape-guiding block 87 if dual-sided recording is desired.
- [0066] Although the later described implementation differs in many aspects from the first implementation, the size of the head is significantly less than the width of the tape in both implementations. The reduced mass of the head allows fast response to positioning errors. The separation between the head and the tape can be controlled even at high tape speeds, while the head and the tape wear are significantly reduced.
- [0067] Both implementations require a separation between the head and the stabilizer while tape is threaded from the supply reel to the take-up reel. *Fig 9* shows the tape 6 between head 80 and stabilizer 86, while *Figs 7a* and *7b* show the tape between flexure 72 with attached head 74 and flexure 76 with attached stabilizer or head 75.

In both implementations the tape 6 is tightly held between the head and the stabilizer. When a reel or a tape cartridge is first loaded onto the tape transport, the free end of the tape must be threaded between the head and the stabilizer. Similarly, before the tape is unloaded from the drive, the tape must be unthreaded. The free end of the tape may be attached to a tape leader or a pin. Most tape drives use a mechanism, such as an arm, to thread the free end of the tape from the supply reel to the take-up reel. The path of the thread mechanism must be unobstructed. A mechanism to move the head out of the thread path is required. Many variations of such a mechanism are possible.

- [0068] In the following the preferred implementation will be described. Although the mechanism will only be described in reference to the first implementation of the invention, it is apparent that with minor modifications the same mechanism can be adapted for the second implementation of the invention.
- [0069] *Fig 12* shows read/write head system 70 with attached solenoid 100. Four rods are movably attached to solenoid 100. Rods 101 and 102 are visible in *Fig 12*. The rods extend through the actuator base 71, as shown by dashed lines. Sloped guides 103 and 104 are attached to flexure 72. Sloped guides are also attached to flexure 76, but are not visible in *Fig 12*. One end of each rod is attached to the solenoid 100 while a second end is free.
- [0070] The solenoid has two positions. *Fig 12* shows the retracted position. The free ends of the rods are outside of the sloped guides in the retracted position. In the retracted position springs 73 and 78 urge flexures 72 and 76 towards each other and read-write head 74 and stabilizer 75 hold tape 6 (not shown) tightly.
- [0071] Figures 13 show a side view. In the side views rods 102 and 105, and sloped guides 104 and 106 are visible. The operation will now be explained with reference to Figures 13.
- [0072] *Fig 13a* shows the retracted position with the free ends of the rods 102 and 105 outside of sloped guides 104 and 106. When the solenoid is activated, the free end of the rods is moved forward as indicated by arrow D3 in *Figs 13b* and *13c*. As the rods move forward, they enter the sloped guides.

[0073] In *Fig 13b* rod 102 has entered sloped guide 104 and rod 105 has entered sloped guide 106 . As the rods move into the sloped guides, the guide 104 is moved in direction of arrows D4 and guide 106 is moved in direction of arrow D5 . This causes the flexures and attached head 74 and attached stabilizer 75 to separate.

[0074] In *Fig 13c* the rods have further entered the sloped guides. The read-write head is further separated from the stabilizer and tape 6 is no longer trapped between the head and the stabilizer. The flexures with the attached head and stabilizer are now moved in direction of arrow D6 by actuator 71 as shown in *Fig 13d*. After the completion of this movement, the head and stabilizer have cleared the thread path . A suitable threading mechanism can now be used to unthread the tape.

[0075] When the tape is first loaded the above operations are performed substantially in reverse. With the head and stabilizer moved out of the threading path of the tape, the tape is threaded through the tape path. Then actuator 71 moves the flexures with the attached head and stabilizer so that the head and the stabilizer are positioned on opposite sides of the tape. Solenoid 100 retracts the rods from the sloped guides and the springs 73 and 78 (as shown in *Fig 7*) urge head 74 towards the stabilizer 75 .

[0076] Although the present invention has been described with reference to preferred embodiments, numerous modifications and variations may be made and the result will still come within the scope of the invention. No limitation with respect to the specific embodiments disclosed herein is intended or should be inferred.